

October, 2016

3M™ Scotch® Cellophane Film Tape 610

Product Description

Scotch® Cellophane Film Tape 610 is a high performance, transparent cellophane film tape featuring a high tack adhesive system. This product offers excellent adhesion, dispensing and handling properties.

Product Features

- Dimensionally stable on the application up to 300°F (140°C)
- Easily dispensed.
- Excellent holding properties.
- Immediate adhesion to a variety of substrates.
- Controlled consistent unwind for reliable hand dispensing.



Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Physical Properties

Property	Values		Method
Color	Transparent		
Total Tape Thickness	0.058 mm	2.3 mil	ASTM D3652
Backing Thickness	0.036 mm	1.43 mil	ASTM D3652
Backing	Cellophane Film		
Adhesive	Pressure Sensitive Rubber Resin		

Typical Performance Characteristics

Property	Values		Method	Substrate
Peel Adhesion	3.3 N/cm	30 oz/in	ASTM D3330	Stainless Steel
Elongation at Break	15 %		ASTM D3759	

Tensile Strength		Test Condition
40.2 N/cm	23 lb/in	Machine Direction
70 N/cm	40 lb/in	Cross Direction

Property: Tensile Strength Method: ASTM D3759

Available Sizes

Property	Values	
Standard Roll Length	66 m	72 yd
Standard Width	6.35, 9.5, 19, 25.4, 38.1, 50.8 mm	1/4, 3/8, 3/4, 1, 1.5, 2 in
Core Size (ID)	76.2 mm	3 in

Storage and Shelf Life

Store under normal conditions of 70° (21°C) and 50% R.H. in the original carton. To obtain best performance, use this product within 18 months from date of manufacture.

Trademarks

Scotch is a registered trademark of 3M.

References

1. 3m.com Product Page

Url: http://www.3m.com/3M/en_US/company-us/all-3m-products/~/Scotch-Light-Duty-Packaging-Tape-610-Heat-Resistant?N=5002385+3293241459&rt=rud

2. Safety Data Sheet

Url: https://www.3m.com/3M/en_US/company-us/SDS-search/results/?gsaAction=msdsSRA&msdsLocale=en_US&co=ptn&q=610

ISO Statement

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.

Technical Information

The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use

Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty, Limited Remedy, and Disclaimer

Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability

Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

