3M™ Peltor™ Technical Datasheet



$3M^{\mathsf{TM}} \overset{\mathsf{Peltor}^{\mathsf{TM}}}{\mathsf{SportTac}^{\mathsf{TM}}}$

Product description

Level dependent hearing protection specially designed for hunters and shooters.

Key Features:

- Specially designed for hunters and marksmen
- Smooth active-volume function that helps prevent the sound being cut off abruptly
- Interchangeable shells makes it easy to change colours
- Automatic shut-off
- Foldable
- Battery life span about 600 hours
- Audio input for an external radio

Versions:

Description Article no Colour MT16H210F-478-GN SportTac (hunting) XH001650049 Orange / olive green MT16H210F-478-RD SportTac (shooting) XH001650056 Black / Red

Accessories and Spare parts:

Description		Art no								
Connection cables										
TAMT06	on cable PTT and microphone,	XH001662747								
	straight contact, 3.5 mm, 2.5 mm.									
TAMT06V	on cable PTT and microphone,	11003064257								
	angled contact, 3.5 mm, 2.5 mm.									
MT661-D Flex	Boom Microphone and PTT ,with 3,5 mm,	XH001676416								
	2,5 m angled contact									
MT661-F Flex	Boom Microphone and PTT, with 3,5 mm,	XH001676473								
	2,5 m straight contact									
FL6H	3.5-mm mono jack	XH001652078								
FL6M	2.5-mm mono jack	XH001652094								
FL6N	3.5-mm stereo jack	XH001652110								
FL6H-31	3.5-mm mono jack for 31 MHz radio	XH001654793								
Hygine Kit										
HY21	Hygiene Kit for SportTac	XH001659305								
Replacement Shells										
210100-478-GN	One pair of replacement shells, green	XH001653290								
210100-478-OR	One pair of replacement shells, orange	XH001653308								
210100-478-SV	One pair of replacement shells, black	XH001653324								
210100-478-RD	One pair of replacement shells, red	XH001653316								
210100-478-VI	One pair of replacement shells, white	XH001653332								



3M[™] Peltor[™] Technical Datasheet

Standards and Approval:

The attenuation values are tested and approved according to PPE directive 89/686 EEC and applicable sections of European Standard EN 352-1:2002, EN 352-4:2001, EN 352-6:2002.

Certificate issued by INSPEC International Ltd,56 Leslie Hough Way, Manchester, England, ID#0194.

This equipment is in conformity with the provisions of Council Directive 89/336/EEC and, where such is the case, with the national standard transposing harmonised standard(s) No: EN55022Class B, EN61000-4-2, EN61000-4-3, EN61000-6-2:2001, EN61000-6-3:2001

Marking:

As the product is in conformity with provisions of Council Directives it carries the CE-mark. The product is also marked in accordance with 89/686/EEC (PPE).

Materials:

Headband wire (stainless steel)
Two-point fastener (headband wire)
Ear cushion (PVC foil and Polyester foam)
Attenuation cushion (Polyester foam)
Headband (stainless steel sheet metal)
Headband padding (PVC)
Cup (ABS)

Technical Data Specifications:

Power: Battery Type: 2 x AAA batteries

Operating time: ~ 600h (depending on battery brand and

temperature)

Net Weight - headband : 318g

Operating temperature: -20 °C to +55 °C (battery dependent)

Storage Temperature: -20 °C to +55 °C

In the Box:

1 x SportTac

2 x AAA Batteries

1 x User Instructions

1 x Extra pair of shells

Attenuation

MT16H210F-478-**

Frequency (Hz)	63	125	250	500	1000	2000	4000	8000
Mean attenuation (dB)		21.1	17.9	27.0	26.8	30.5	38.3	36.4
Std deviation (dB)		4.3	3.1	3.8	3.0	3.0	3.7	5.4
Assumed Protection Value (dB)		7.8	14.8	23.2	23.8	27.5	34.6	31.0

SNR=26 db H=29 db M=23 db L=16 db

Important Notice:

3M does not accept liability of any kind, be it direct or consequential (including, but not limited to, loss of profits, business and/or goodwill) arising from reliance upon any information herein provided by 3M. The user is responsible for determining the suitability of the products for their intended use. Nothing in this statement will be deemed to exclude or restrict 3M's liability for death or personal injury arising from its negligence.



3M Occupational Health & Environmental Safety Division 3M Svenska AB, Box 2341 SE-331 02 Värnamo Sweden Phone: +46 (0) 370 65 65 65 Fax: +46 (0) 370 65 65 99

Email: peltorcommunications@mmm.com Internet: www.3M.com/Peltorcomms